

## TECHNICAL DATA SHEET

### AKSOIL SUPERMAX 4T 15W/40

#### PRODUCT DESCRIPTION

AKSOIL SUPERMAX 4T 15W/40 is engine oil that produced for four stroke motorcycles and it indicates high performance additives. It perfectly protects the engine by minimizing the viscosity change in high temperatures. It is safely used in four seasons for four stroke and high performance motorcycles. Also it is suitable for all kinds of European and Japan production motorcycles that recommended for API SG and/or JASO MA specifications.

#### PROPERTIES

- Excellent antiwear properties protect vital engine and gear components leading to reduced maintenance costs
- Good thermo-oxidative stability prevents harmful deposit formation and controls oil thickening facilitating extended engine and oil life
- Controlled frictional properties eliminate clutch slippage and improves drivability
- Better detergency/ dispersancy keeps engine cleaner and reduces maintenance costs
- Effective rust and corrosion inhibition property ensures longer life of critical engine components

#### APPROVAL AND SPECIFICATIONS

- API SL • JASO MA2

#### TECHNICAL SPECIFICATIONS

TEST	UNIT	METHOD	TYPICAL VALUES
K. Viscosity, @ 100 °C	cSt	ASTM D 445	15.1
Viscosity Index	-	ASTM D 2270	130
Flash Point	°C	ASTM D 92	230
Pour Point	°C	ASTM D 97	-27

\*The above values may vary slightly according to production.

#### HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

It should not be in contact with the skin and eyes, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, should be washed with plenty of water and medical attention should be sought if necessary. If swallowed, the victim should not be induced vomiting and immediate medical attention should be sought. If vapor is inhaled, plenty of breath should be taken in fresh air and, if necessary, medical attention should be sought. Used oils should not be disposed to garbage, sewage or receiving environment, they should be collected in waste oil collection containers complying with the legislation, and delivered to the manufacturer or licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in stove and boilers. It should be kept out of the reach of children. Empty containers should not be thrown to the garbage or left in the receiving environment, they should be delivered to licensed recycling companies.

For detailed information, you can review the "Material Safety Data Sheet".

#### STORAGE CONDITIONS

Packages should not be exposed to long-term and direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 °C. It is the sole responsibility of the user to use this product for its intended purpose and to comply with applicable laws and regulations. ALKİM PETROKİMYA SAN ve TİC A.Ş. cannot be held responsible for any damage or loss that may result from the abnormal or improper use of the product, or for the dangers in the structure of the product and for its consequences.

#### TYPES OF PACKING

